

H.264 HD Series
DVR HHD-916

H.264 HD Real-Time DVR




Main Features

- One HD (1280x720) Analog Camera and Eight D1 (720x480) Analog Cameras Supported
- High Definition Picture Quality
- True HD Triple Streaming for Live Display, Playback, and Recording
- CMS Supports E-Map
- Mac System Supported
- Touch-Panel LCD Monitor Supported
- 3G Mobile System Supported
- Support for 3 Internal HDD
- User Friendly GUI



720 x 480



Other
Indistinct



1280 x 1024



iCATCH
Distinct



Model		HHD-916	
Camera Input		9CH	
Video	HDMI	1 (Option) {Video Output [1280x1024] + Audio Output}	
	Input	HD-SDI camera x1 + (720x480 / 720x576) analog camera x 8	
	Output	1VGA (1280x1024) + 1BNC (720x480 / 720x576) for Co-monitor 1VGA (1280x1024) + 1BNC (720x480 / 720x576) for SPOT Monitor	
Audio	Input	8 RCA + 1 x HD-SDI	
	Output	2RCA	
System	Operating System	Embedded Linux OS	
	Internal HDD	Supports Max. x 4 SATA Devices (HDDx3+eSATAx1, HDDx2+DVDx1+eSATAx1)	
	External HDD	YES (eSATA)	
	Sensor In (NO, NC) Relay out	Sensor-in x9 Relay-out x2	
	Serial Interface	RS-485	
	USB	2 x USB2.0	
	Dimension (mm)	430(w)x55(h)x293(d)	
	Weight (w/o / HDD/DVD±RW)	1.85KG	
	Adaptor	Input 100~240V, Output 12V 6A	
	Power Source	72W	
Display	Speed	HD 30fps, D1 240 fps (NTSC) / 200 fps (PAL)	
	Resolution (Pixel)	1280 x 720 / 720 X 480(NTSC), 720 X 576(PAL)	
	Split Screen	1, 4, 9, SEQ.	
	Auto Channel Switching	Switching time : 1 ~ 999 sec	
	Mode	Zoom (Digital x2~ x8), PIP, Auto SEQ.	
Recording	Compression	H.264 ASP (Internet Transmission: H.264)	
	Dual Stream Resolution (Pixel)	Main (Recording)	1280 x 720 / 704 X 480, 704 X 240, 352 X 240 (NTSC) / 704 X 576, 704 X 288, 352 X 288 (PAL)
		Sub (Network)	352 x 240, 176 x 120 (NTSC), 352 x 288, 176 x 144 (PAL)
	Picture Quality	5 levels (Highest, High, Normal, Basic, Below Basic)	
	Mode	Manual, Motion, Sensor, Schedule	
	Speed	NTSC Max. HD 30 fps (for CH 1) & D1 45 fps (for CH 2 ~ CH 8) or Max. D1 120 fps (for 9 Channels) PAL Max. HD 30 fps (for CH 1) & D1 37 fps (for CH 2 ~ CH 8) or Max. D1 100 fps (for 9 Channels)	
	Pre-Alarm	10 SEC	
	Post-Alarm	1 ~ 60 SEC	
	Water Mark	YES	
	Playback	Display	1, 4, 9
Search mode		Date, time, event(Motion, Sensor), camera	
Zoom		Digital (x2 ~ x8)	
Snapshot		YES	
Speed		Normal, REW & FF (speed x2, x4, x8, x16, x32, x64), Frame to frame, Pause	
Device		Int. HDD	
Network	Network Interface	10/100 Ethernet	
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP	
	Application	Windows XP/VISTA/7(PC Client system)	
	Remote Software	Licensed Application Software, IE Browser	
	Account	1 Admin + 4 users	
	CMS	Unlimited (Depends on bandwidth)	
	3G / GPRS	Symbian, Windows Mobile, BlackBerry, iPhone, Android phone	
Backup	Event Transport	E-mail	
	Interface	USB 2.0 or SATA	
	Audio Backup	YES	
	Network	YES	
Alarm	Backup Device (Optional)	Network Backup / USB / Flash Drive / USB DVD±RW / SATA DVD±RW	
	Motion Detection	Detected Frames: Unlimited / Channel	
		Sensitivity : 10 levels for each channel Area : Programmable individually	
	Search (Event Criterion)	YES	
OSD & DVR Control	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)	
	GUI	16-bit True Color	
	Multi-Language	English, Traditional Chinese, Others	
	Camera Title	Multi-Language	
	USB Mouse	YES	
	Touch Panel	Touch Panel LCD Monitor(USB Interface, EETI Chipset Only)	
	Remote Controller	IR Remote Control (Max. 4 Device)	
	System Upgrade	via USB / Network	
Pan / Tilt / Zoom / Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LILin)		

H.264 HD Series DVR HHD-916

SUBJECT CHANGED WITHOUT NOTICE



iCATCH
You Are Secure.

iCatch Inc. www.icatchinc.com

2F, No. 26, Lane 513, RuiGuang Road, NeiHu District Taipei, Taiwan 114

Tel: 886-2-5550-6660 Fax: 886-2-5550-6670