



*Simple to use*

Convenient Network Recorder

*The ideal network video recording solution for your business safety*

# FXR-2000NV

4 Channel Network Video Recorder

- Real-time Mega-pixel recording
- Multi-codec support (H.264, MPEG-4, MJPEG)
- E-map & Google map support
- Multi-channel playback
- 3G Mobile phone viewer (iPhone, Blackberry, Windows Mobile)





## 4 Channel Network Video Recorder

# FXR-2000NV



### Specification



| Model No.         |   | FXR-2000NV   |              |
|-------------------|---|--|--------------|
| Camera Input      |   | Max. 4pcs IP camera  |              |
| Support Cameras   |   | Fulix, Abus, ACTi, Arecont Vision, AVTECH, AXIS, A-MTK, A-Linking, Brickcom, Canon, D-Link, Etrivision, Hunt, IQInvision, Level 1, Mobotix, Panasonic, Pixord, Planet, Sony, Toshiba, Vivotek, Zavio |              |
| Recording         | Recording frame rate                          | up to 120fps @ 1.3M (18Mbps)   |              |
|                   | Compression                                   | H.264, MPEG-4, MJPEG   |              |
|                   | Resolution                                    | Mega-pixel, HD, D1, CIF, QCIF  |              |
|                   | Recording mode                                | Manual, Schedule, Continuous, Event  |              |
|                   | Pre/Post alarm Rec.                           | Support  |              |
| Live view         | Audio   | up to 4 channels   |              |
|                   | Screen mode                                   | 1/4 split screen, Full screen mode   |              |
|                   | Snapshot                                      | Support (JPEG)   |              |
|                   | Digital PTZ                                   | Support  |              |
|                   | E-map   | Support (Local e-map, Google map)  |              |
| Playback          | Event popup                                   | Support (Motion detected event pop-up display on E-map)  |              |
|                   | Multi-channel playback                        | Support (1/4 split screen, Full screen mode)   |              |
|                   | Playback speed                                | Frame by frame, FF and REW (x-32~x32)  |              |
|                   | Search method                                 | Time search, Event search  |              |
| Networking        | AVI export                                    | Support  |              |
|                   | Network port                                  | RJ-45, Gigabit Ethernet  |              |
|                   | Network connection                            | Static IP, DHCP  |              |
|                   | Emergency notification                        | HTTP / FTP / E-mail  |              |
|                   | NTP   | Support  |              |
|                   | DHCP server                                   | Support  |              |
|                   | Two-way audio                                 | Support  |              |
|                   | CMS   | -  |              |
| IE Viewer         | Support (Max.4 users can access concurrently) |  |              |
| Setup             | 3GPP  | Support<br>(PDA(Windows Mobile 6.5), i-Phone, Blackberry, Symbian S60)   |              |
|                   | Easy Setup                                    | UPnP, Camera auto-searching function   |              |
|                   | Data auto deletion                            | Support  |              |
|                   | DST   | Support  |              |
|                   | User management                               | Multi user / group support   |              |
| I/O               | Languages                                     | 15 languages   |              |
|                   | RS-232C                                       | -  |              |
|                   | RS-485  | -  |              |
|                   | UPS connection                                | -  |              |
| Storage           | USB interface                                 | 2 ports (USB 2.0)  |              |
|                   | DI/DO   | -  |              |
| H/W specification | HDD   | Max. 2 internal HDDs (up to 3TB)   |              |
|                   | Dimension                                     | 126(W)*220(D)*78.2(H)  |              |
|                   | Weight  | 3.0kg  |              |
|                   | Temperature                                   | Operating  | 5°C ~ 40°C   |
|                   |   | Storage  | -20°C ~ 70°C |
|                   | Humidity                                      | Operating  | 10% ~ 80%    |
|                   |   | Storage  | 5% ~ 90%     |
| Power supply      | 12V DC, 4A                                    |  |              |
| Power consumption | 50W   |  |              |
| Certification     | CE, FCC                                       |  |              |